



## Xorel Circuit

6877

\$43.00 /yd.

A \$3.00 per yard cut charge applies to orders under 50 yards

### Upholstered Walls/Panels Specifications

**Type:** Acoustical, Moveable Walls (backing requirements vary by manufacturer), Tackable, Wrapped Panels, Xorel Artform

**Backing:** Unbacked

**Backing Note(s):** Acrylic: This backing provides a coating to enhance adhesion and prevent bleed through of adhesives (15 yard minimum), Heavy Acrylic: This backing provides a coating to enhance adhesion and prevent bleed through of adhesives and is preferred for heavier duty installs such as moveable wall systems (15 yard minimum), Unbacked: Acoustically transparent, highly tackable, ability to self heal, yarns can "move back" into position. Highly stable on panels and does not react to changes in humidity or moisture.

**Available Backing(s):** Acrylic, Heavy Acrylic

**Finish(es):** Finish-Free

**Width:** 56" (142 cm)

**Weight per Linear Yard:** 12 oz

**Contents:** 100% IFR Xorel®

**Cleaning Code:** WS & BC - Water/Solvent & Bleach Cleanable

**Flammability:** ASTM E84 Class A / Class 1, FAA 25.853 (a&b), Fabric meets Underwriters Laboratories (UL) 1286 Flammability Requirements for Office Furnishings, NFPA 265 Room Corner Test, NYC 294-40 SR

**Acoustics:** NRC of 1.05 when wrapped around a 2" thick panel, Test Method ASTM C 423

**Manufactured In:** EU

**Warranty:** 10 years

**ACT Symbols:** 

Programs/Partnerships

**Program Guidelines:** GSA

Sustainability

**Standards and Certifications:** Cradle to Cradle Certified Silver, LEED, MindClick Rated - Leader, Mindful Materials, SCS Indoor Advantage™ Gold

**Free of:** Antimicrobials, Bisphenol A (BPA), Chlorine, DMF, Fluorocarbons, Formaldehyde, Heavy metals, Ozone-depleting chemicals, PFC, Phthalates, Plasticizers, PVC, Solvents, Stain resistant finishes

**Additional Details:** Extremely low VOCs, Inherently Antimicrobial - In accordance with Test Method AATCC 147, No topical finishes, Responsible Return Program, Safely Disposable

Colors

