Flux 6557



USES

Panels Upholstered Walls Upholstery Wallcovering Xorel Artform Museum Display Cases

## CONTENTS

100% IFR Xorel®

Carnegie Xorel<sup>®</sup>

Flux 6557

USES Panels, Upholstered Walls, Upholstery, Wallcovering, Xorel Artform,

Museum Display Cases

BACKINGS/WIDTHS Unbacked 56 in / 142 cm

> Acrylic Backed 54 in / 137 cm 54 in / 137 cm X-Protect Sit™ X-Protect Wall™ 52 in / 132 cm

**CONTENTS** 100% IFR Xorel®

**FINISH** Finish Free

ASTM E84 Class A / Class 1, Fabric meets Underwriters Laboratory(UL) 1286 FLAME RETARDANCY

> Flammability Requirements for Office Furnishings, FAA 25.853 (a&b), NYC 294-40 SR, NFPA 260 Class 1, California Technical Bulletin 117 - 2013,

NFPA 265 Room Corner Test, Canadian ULC S102

**DURABILITY** No wear 1 million double rubs\*

**ECO INFO** Cradle to Cradle Certified<sup>CM</sup> Silver

facts<sup>CM</sup> Certified Silver

LEED

SCS Indoor Advantage™ Gold

Free of Antimicrobials, Antimony, Bisphenol A (BPA), Chlorine, DMF, Fluorocarbons, Formaldehyde, Halogenated fire retardants, Heavy metals, Ozone-depleting chemicals, PFC, Phthalates,

Plasticizers, PVC, Solvents, Stain resistant finishes Free from harmful substances / Oddy Test

No topical finishes

Antimicrobial, Antibacterial, Safely Disposable, Extremely low VOCs

**ACOUSTICS** NRC of 1.05 when wrapped around a 2" thick panel

Test Method ASTM C 423

**CLEANING CODES** WS & BC - Water / Solvent & Bleach Cleanable

**NOTES** X-Protect: Proprietary Xorel backing technology which prevents stains and moisturefrom

passing through the textile enabling the wall or seating surface to be aggressively cleaned

A summary of the results of 65 independent tests on Xorel is available

at carnegiefabrics.com

\*Results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.









