



10




2



9



1



6




11



8




4



5



7



3

USES
Panels
Upholstered Walls
Wallcovering
Xorel Artform
Museum Display Cases

CONTENTS
100% Xorel®
(58% PE, 42% Biobased PE)

Carnegie Xorel®

USES	Panels, Upholstered Walls, Wallcovering, Xorel Artform, Museum Display Cases
BACKINGS/WIDTHS	Unbacked 56 in / 142 cm Acrylic Backed 54 in / 137 cm X-Protect Wall™ 52 in / 132 cm
CONTENTS	100% Xorel® (58% PE, 42% Biobased PE)
FINISH	Finish Free
FLAME RETARDANCY	ASTM E84 Class A / Class 1, Fabric meets Underwriters Laboratory(UL) 1286 Flammability Requirements for Office Furnishings, NFPA 265 Room Corner Test, NYC 294-40 SR, NFPA 260 Class 1, California Technical Bulletin 117 - 2013, Canadian ULC S102
ECO INFO	Cradle to Cradle Certified ^{CM} Silver facts ^{CM} Certified Silver LEED SCS Indoor Advantage TM Gold USDA Certified Biobased Product Free of Antimicrobials, Antimony, Bisphenol A (BPA), Chlorine, DMF, Fluorocarbons, Formaldehyde, Halogenated fire retardants, Heavy metals, Ozone-depleting chemicals, PFC, Phthalates, Plasticizers, PVC, Solvents, Stain resistant finishes Free from harmful substances / Oddy Test No topical finishes Antimicrobial, Antibacterial, Safely Disposable, Extremely low VOCs Responsible Return Program 42% Biobased content derived from rapidly renewable plant based resources TUV Austria OK biobased - Level 2 (ASTM D6866)
ACOUSTICS	NRC of 1.05 when wrapped around a 2" thick panel Test Method ASTM C 423
CLEANING CODES	WS & BC - Water / Solvent & Bleach Cleanable
NOTES	X-Protect: Proprietary Xorel backing technology which prevents stains and moisture from passing through the textile enabling the wall or seating surface to be aggressively cleaned A summary of the results of 65 independent tests on Xorel is available at carnegiefabrics.com *Results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.

