



## ***CERTIFICATE OF TESTING***

For The Account Of: **Carnegie**  
110 North Centre Avenue  
Rockville Centre, NY 11570  
Contact: Nikki Rubalcaba

DATE: December 27, 2002      CERTIFICATE (ORDER) NO.: 99298

CLIENT'S IDENTIFICATION: **Ponte**


Test Performed: **NFPA 701 - Standard Methods of Fire Tests for  
Flame Resistant Textiles and Films - 1996 Edition - Test #1**

***CERTIFICATION:***    The textile sample named above was tested and  
**PASSED** the NFPA 701 Test #1 - 1996.

A.C.T. Standard: *Drapery - Must Pass*

This laboratory test is not intended to reflect fabric performance under actual fire conditions. The certification procedure merely measures the performance of samples under the predetermined and specific test conditions prescribed by the standard specified. This certificate applies only to the standards or processing identified and to the random sample(s) tested. The test results are representative of the qualities of the piece or lot only to the extent the sample tested is representative of the piece or lot. Our reports and letters are for the exclusive use of the customer to whom they are addressed, and they and the corporation names above or its seals or insignia are not to be used under any circumstances without our prior written approval. Samples will not be retained, unless specified by the customer. Retained samples will be kept a maximum time of one year unless a specific retention period is necessary.

**CERTIFICATION:** I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 701 1996 Edition Test # 1 Procedure.

  
Sallie Cotey - Laboratory Manager  
Applied Textiles Lab Services

Page 1 of 2

**DATA SHEET**

<b>Specimen #</b>	<b>Initial Mass(g)</b>	<b>Final Mass(g)</b>	<b>% Weight Loss</b>	<b>Flaming Drip Seconds</b>
1	13.9	11.0	21	0
2	13.9	10.9	22	0
3	13.8	11.3	18	0
4	14.0	10.7	24	0
5	13.7	11.8	14	1
6	13.8	9.6	30	0
7	14.1	11.5	18	0
8	13.9	10.4	25	1
9	13.7	12.0	12	1
10	13.8	11.9	14	0
<b>AVG</b>	<b>13.9</b>	<b>11.1</b>	<b>20%</b>	<b>0.3</b>

Approximate weight (oz./sq. yd): 6.75

**PERFORMANCE CRITERIA:**

1. Where fragments or residues of specimens that fall to the floor of the test chamber continue to burn for more than an average of 2 seconds per specimen for the sample of 10 specimens, the material shall be recorded as failing.
2. Where the average weight loss of the 10 specimens in a sample is greater than 40 percent, the material shall be recorded as failing.
3. Where the specimens do not demonstrate performance in accordance with either of the conditions indicated above, the material shall be recorded as passing this test and shall be designated as flame resistant.

**CONCLUSION:** Based on the above Results and Performance Criteria, the item tested:

  x   Passes  
      Fails

Page 2 of 2